

FTB OPTION CODES

CODE	DESCRIPTION	LIST ADDER/ (DEDUCT)
000	STANDARD FEATURES: FULLY INSULATED CABINET, GALVANIZED STEEL CABINET WITH PAINTED FRONT PANELS, DIRECT DRIVE FLEX MOUNTED MULTI SPEED BLOWER, SEQUENCER CONTROLLED HEATING ELEMENTS, CHECK STYLE FLOWRATER USED FOR A/C AND HEAT PUMPS, BOTTOM PRIMARY & SECONDARY DRAIN W/ RIGHT SIDE PRIMARY, ALL DRAIN CONNECTIONS 3/4" FPT WITH PLUGS IN ALL DRAINS, CIRCUIT BREAKER DISCONNECT, FRONT OR BOTTOM RETURN AIR POSITION, FILTER RACK AND DISPOSABLE FILTER, FAN TIME DELAY RELAY, OFFSET HANGING BRACKETS INCLUDED, HIGH EFFICIENCY COPPER TUBE / ALUMINUM FIN COIL INCLUDES STANDARD LOW LEAK FEATURES-SEALS AROUND DRAIN OUTLET, GROMMETS AROUND LIQUID LINE AND SUCTION LINE ENDS(3/8 & 7/8).	\$0
001	PERFORATED BOTTOM FRONT DOOR	\$6
002	TERMINAL BLOCK – 10KW & BELOW	(\$10)
003	Schrader on suction line inside cabinet	\$4
004	discontinued option effective 6/6/03 - PULL-OUT DISCONNECT	\$0
005	PERFORATED BOTTOM FRONT DOOR; TERMINAL BLOCK	(\$4)
006		
007	discontinued option effective 6/6/03 - PERFORATED BOTTOM FRONT DOOR, PULL-OUT DISCONNECT	\$0
008	PERFORATED BOTTOM FRONT DOOR, TERMINAL BLOCK, FTBXX30 WITH 1/5HP BLOWER MOTOR, #59 PISTON.	(\$4)
009	FTBXX 30 WITH 1/5 H.P. BLOWER MOTOR; WITH SPECIAL STICKER ON UNIT AND PACKAGING STATING: "FOR USE WITH 1.5 & 2 TON SYSTEMS ONLY"	\$0
010		
011		
012	FTBXX 30 WITH 1/5 H.P. BLOWER MOTOR; #55 PISTON (ONLY FOR USE WITH A 1.5-TON HEAT PUMP CONDENSER)	\$0
013	FTBXX 30 WITH 1/5 H.P. BLOWER MOTOR; #59 PISTON (ONLY FOR USE WITH A 2-TON HEAT PUMP CONDENSER)	\$0
014	discontinued option effective 7/7/03 - PERFORATED BOTTOM FRONT DOOR; 1/5 HP BLOWER MOTOR	\$0
015	FRONT DOOR REFRIGERANT CONNECTIONS	\$16
016	FRONT DOOR REFRIGERANT CONNECTIONS, PERFORATED BOTTOM FRONT DOOR	\$22
017	ENHANCED LOW LEAK KIT--INSULATION STRIP AROUND CABINET FACE PERIPHERY AND TOP EDGES	\$8