


373 ATASCOCITA RD. • HUMBLE, TX • 77396 TEL (281) 441-6500 • FAX (281) 441-6510

<< www.aspenmfg.com >>

DIMENSIONS AND SPECIFICATIONS Aspen VersaCoil Cased Multi-Position Coils

Designed for York P1FM Furnaces



GENERAL SPECIFICATIONS

(Coil shown in vertical configuration with front access panel removed.)

- Standard refrigerant connections: liquid line 3/8" ODS, suction line 7/8" ODS.
- · Right-hand refrigerant and plumbing connections.
- Three 3/4" MPT condensate drains. Dual drain in vertical or horizontal position.
- No field-modification required for multi-position applications.
- · Factory pre-installed powder-painted metal drain pan. Stainless available.
- Five-year warranty.
- Flowrater standard. Factory or field-installable TXV available.
- · Front access panel for easy service.
- Every coil immersion-tested at 500 psi, then nitrogen-pressurized and sealed.
- Heavy guage embossed galvanized cabinets fully lined with 1/2" faced insulation.
- Flush-fits furnace in most applications.
- · Rifled copper tubing, enhanced aluminum fins.
- ARI certifiable with all brands of A/C and heat pump systems.
- · ETL listed.

YORK OIL	ASPEN				BOTTOM		TOP		
FURNACE	COIL		FOOTPRINT		OPENING		OPENING		HEIGHT
MODEL	MODEL	SUFFIX	Α	В	С	D	Е	F	G
P1FMD12F05501	BV1** 30	BYG21	20	21	18-1/4	17-1/4	18-1/4	17-1/4	21
P1FMD12F08501	BV1** 36	BYG25	20	21	18-1/4	17-1/4	18-1/4	17-1/4	25
	BV5** 36	BYG21	20	21	18-1/4	17-1/4	18-1/4	17-1/4	21
	BV1** 42	BYH25	22	23-3/4	20-1/4	22-1/4	20-1/4	22-1/4	25
	BV5** 42	BYH25	22	23-3/4	20-1/4	22-1/4	20-1/4	22-1/4	25
P1FMD16F10001	BV1** 48	BYH29	22	23-3/4	20-1/4	22-1/4	20-1/4	22-1/4	29
P1FMD20F12501	BV5** 48	BYH25	22	23-3/4	20-1/4	22-1/4	20-1/4	22-1/4	25
	BV1** 60	BYH29	22	23-3/4	20-1/4	22-1/4	20-1/4	22-1/4	29
	BV7** 60	BYH29	22	23-3/4	20-1/4	22-1/4	20-1/4	22-1/4	29
	BV2** 60	BYH29	22	23-3/4	20-1/4	22-1/4	20-1/4	22-1/4	29