CX SERIES COILS

DEDICATED HORIZONTAL COPPER COIL



Unit shown with service panels removed. Representative image only. Some models may vary in appearance.

STANDARD FEATURES

- · Rifled copper tubing, enhanced aluminum fins.
- Immersion tested at 500 psi, followed by nitrogen pressurization and factory sealing to ensure optimal system integrity and long-term reliability.
- Refrigerant lines exit top of coil. Schrader valve on suction line for pressure assurance testing. Refrigerant and plumbing connections:
 - o All Drain Pan Connections: 3/4" NPT
- · Heavy duty polypropylene drain pans.
- Inlet and outlet opening dimensions are identical (without end caps).
- · Three-piece service door on top for easy service access.
- · Fully insulated cabinets with faced insulation.
- ETL listed for R22, R410A, R454B, and R32 refrigerants (A2L Refrigerants certified with Refrigerant Detection System (RDS)).
- A2L refrigerants require a Refrigerant Detection System (RDS) for compliance.
- · AHRI certifiable with all brands of A/C and heat pump systems.

WARRANTY

• Ten-year limited warranty with registration.

CUSTOMIZATION OPTIONS*

UNIVERSAL A2L REFRIGERANT TECHNOLOGY FOR R32 & R454B SYSTEMS



IDEAL FOR USE WITH BOTH CASED AND UNCASED COILS, PLUS ALL AIR HANDLERS!

Versa Plus™ coils are easily configurable for use with either R32 or R454B refrigerant with proper metering device. Utilizing universal Refrigerant Detection Systems (RDS) to ensure regulatory compliance.

OTHER POPULAR CUSTOM OPTIONS:

Refrigerant Detection System (RDS) kit factory-installed.

· Factory or field-installed TXV available.

















In keeping with its commitment to continuous improvement. Aspen Manufacturing reserves the right to make changes without notice and incurring obligation. To stay up-to-date with this product and Aspen's trusted line of coils, air handlers, and more, go to our website. © 2025 Aspen Manufacturing. All Rights Reserved


Phone: 281.441.6500 Toll Free: 800.423.9007 Fax: 281.441.6510 Customer Service: info@aspenmfg.com Warranty Team: warranty@aspenmfg.com



FIGURE 1







(REFERENCE ONLY)

DIMENSIONAL DATA (In.) - FIGURE 1											
COIL MODEL	NOM. CAPACITY	DIMENSIONS							SHIPPING INFO.		
		CABINET				OPE	WEIGHT (LBS)				
		WIDTH	DEPTH	MAX. HEIGHT	TRANSITION HEIGHT AVAILABLE OPTIONS	WIDTH	HEIGHT	# (# OF ROWS		
	BTU	Α"	В"	C"	T"	D"	E"	2	3	4	
CX24A*	24,000	21	22	14-1/2	14 / 14-1/2	20	13-1/2	-	35	39	16
CX24B*		21	22	15	14 / 14-1/2 / 15	20	14	-	37	42	16
CX24E*		21	27	17-1/2	14 / 14-1/2 / 17-1/2	20	16-1/2	43	50	57	16
CX30A*	30,000	21	22	15	14 / 14-1/2 / 15	20	14	-	37	42	16
CX30E*		21	27	17-1/2	14 / 14-1/2 / 17-1/2	20	16-1/2	-	50	57	16
CX36A*	36,000	21	22	15	14 / 14-1/2 / 15	20	14	-	37	42	16
CX36B*		21	27	17-1/2	14 / 14-1/2 / 17-1/2	20	16-1/2	-	47	53	16
CX36C*		21	22	17-1/2	14 / 14-1/2 / 17-1/2	20	16-1/2	-	41	47	16
CX36D*		21	32	21	14 / 14-1/2 / 17-1/2 / 21	20	20	-	66	75	6
CX36E*		21	27	21	14 / 14-1/2 / 17-1/2 / 21	20	20	-	56	65	12
CX36F*		21	27	17-1/2	14 / 14-1/2 / 17-1/2	20	16-1/2	1	47	53	16
CX42C*	42,000	21	27	21	14 / 14-1/2 / 17-1/2 / 21	20	20	-	58	67	12
CX42D*		21	32	21	14 / 14-1/2 / 17-1/2 / 21	20	20	-	65	74	6
CX48A*	48,000	21	27	17-1/2	14 / 14-1/2 / 17-1/2	20	16-1/2	-	49	56	16
CX48B*		21	27	21	14 / 14-1/2 / 17-1/2 / 21	20	20	-	56	64	12
CX48C*		21	27	21	14 / 14-1/2 / 17-1/2 / 21	20	20	-	56	65	12
CX48D*		21	32	21	14 / 14-1/2 / 17-1/2 / 21	20	20	-	66	75	6
CX60A*	60,000	21	27	21	14 / 14-1/2 / 17-1/2 / 21	20	20	-	58	67	6
CX60B*		21	32	21	14 / 14-1/2 / 17-1/2 / 21	20	20	-	66	75	6
CX60C*		21	32	24-1/2	21 / 24 / 24-1/2	20	23-1/2	-	77	90	6
CX60D*		21	32	25	21 / 24 / 24-1/2 / 25	20	24	-	79	91	6
CX60E*		21	32	25	21 / 24 / 24-1/2 / 25	20	24	-	82	95	6
CX60F*		21	32	24-1/2	21 / 24 / 24-1/2	20	23-1/2	-	69	79	6

DRAIN PAN TEMPERATURE TABLE							
DRAIN PAN TYPE	TEMPERATURE LIMITS						
Plastic - Standard	290°						

HELPFUL LINKS



VIEW PRODUCT ONLINE

For full warranty terms and conditions, please refer to the Warranty Information section on Aspen's official website.



VIEW VERSA PLUS™ ONLINE

Learn more about Aspen's A2L Refrigerant Technology for R32 and R454B Systems.

In keeping with its commitment to continuous improvement. Aspen Manufacturing reserves the right to make changes without notice and incurring obligation. To stay up-to-date with this product and Aspen's trusted line of coils, air handlers, and more, go to our website. © 2025 Aspen Manufacturing. All Rights Reserved

Phone: 281.441.6500 Toll Free: 800.423.9007 Fax: 281.441.6510 Customer Service: info@aspenmfg.com Warranty Team: warranty@aspenmfg.com

