



### Product Features and Specifications

- Rifled aluminum tubing, enhanced aluminum fins.
- Multi-stage leak testing with high pressure testing at 500 psi, mass spectromete pressure decay with helium, then sealed and nitrogen pressurized.
- Left- or right-hand refrigerant and plumbing connections.
- Heavy duty plastic drain pans.
- Embossed galvanized cabinets standard with painted options to OEM color.
- Upflow standard; downflow with field-installed kit, sold separately.
- Cabinets fully insulated foil-faced insulation.
- Split access doors in front of cabinet for easy service access.
- AHRI certifiable with all brands of A/C and heat pump systems.
- ETL listed for use with R-22, R-410A, R-454B, and R-32 when proper metering device is used.
- Ten-year limited warranty. For complete warranty details, please visit [www.AspenMfg.com](http://www.AspenMfg.com)

### Customization

- Factory or field-installed TXV available
- High temperature palstic drain pan
- OEM color matched cabinets

### Downflow Kit Part Numbers

- METAL DRAIN PANS**    **PLASTIC DRAIN PANS**
- 16" DWNFLWM-16    • DWNFLWP
  - 18" DWNFLWM-18

Unit shown with service panels removed. Representative photo only. Some models may vary in appearance. Duct opening dimensions can be ascertained by subtracting 1-1/2" for top opening width/depth, 3/4" for bottom opening.

COIL MODEL	NOMINAL CAPACITY (BTUs)	CABINET DIMENSIONS				SHIPPING INFORMATION			
		MIN. WIDTH	MAX. WIDTH (W)"	DEPTH (D)"	HEIGHT (H)"	WEIGHT (LBS)			SKID QTY
						2 ROW	3 ROW	4 ROW	
DC25A*	24,000	14	21	21-1/2	16	25	28	33	20
DC25B*					28	37			
DC25C*					20	32		42	
DC25D*					36	48			
DC25E*					41	49			
DC31A*	30,000	14	21	21-1/2	16	28	28	37	20
DC31B*					20	32		42	
DC31C*					36	48			
DC31D*					41	49			
DC31E*	45	53	12						
DC37A*	36,000	17		24-1/2	20	32	28	42	16
DC37B*					36	48			
DC37C*					24	41		49	
DC37D*			45		53				
DC37E*			46		63				
DC43A*	42,000	17	24-1/2	21-1/2	20	36	28	48	16
DC43B*					24	41		49	
DC43C*					45	53			
DC43D*					46	63			
DC43E*					50	67			
DC49A*	48,000	21	24-1/2	21-1/2	24	41	28	49	12
DC49B*					45	53			
DC49C*					28	46		63	
DC49D*					50	67			
DC49E*					56	77			
DC61A*	60,000	21	24-1/2	21-1/2	28	46	28	63	12
DC61B*					50	67			
DC61C*					53	72			
DC61D*					56	77			

Notes: 1) Do not use plastic drain pans on oil furnaces or other applications where outlet temperatures may exceed 290 F. Specialty metal drain pans used for these applications.  
 2) For all coils – Liquid line 3/8 ODS; suction line 3/4" ODS for DC24-36, 7/8" for DC42-60.

DC HE Spec-2024-12

In keeping with its commitment to continuous improvement, Aspen Manufacturing reserves the right to make changes without notice and incurring obligation.

**DRAIN PAN TEMPERATURE TABLE**

DRAIN PAN TYPE	TEMP LIMITS
Plastic - Standard	290°
Plastic - High Temp	425°
Metal - High Temp	600°

**ASK FOR ASPEN**

DC HE Spec-2024-12

In keeping with its commitment to continuous improvement, Aspen Manufacturing reserves the right to make changes without notice and incurring obligation.