

CE SERIES

CASED COPPER MULTI-POSITION EVAPORATOR COIL

FEATURES, BENEFITS, DIMENSIONS, & SPECIFICATIONS



Unit shown with service panels removed. Representative drawing only. Some models may vary in appearance. Due to continuous product improvement, specifications are subject to change without notice.

FEATURES AND BENEFITS:

- Rifled copper tubing, enhanced aluminum fins.
- Left or right-hand refrigerant and plumbing connections.
 - Liquid line - 3/4" ODS
 - Suction line - 3/4" ODS on 1.50 3-ton and 7/8" on 3.50-ton to 5-ton.
- Externally mounted flowrater body with Schrader valve for hiss-testing.
- Heavy duty plastic drain pans on most models, powder coated galvanized steel horizontal drain pans standard on all.
- Immersion-tested at 500 psi, then sealed and Nitrogen pressurized.
- Upflow, horizontal right, or horizontal left without field modification. Downflow applications require plate kit, sold separately.
- Split access doors in front of cabinet for easy service access.
- Fully insulated cabinets with foil-faced insulation.
- AHRI certifiable with all brands of A/C and heat pump systems.
- ETL listed for use with R-410A, R-454B, R-22, and R-32 when proper metering device is used.
- Ten-year limited warranty.

CUSTOMIZATION

- Factory or field-installed TXV available.
- Powder-painted metal or stainless pans.
- Painted cabinets.
- Schrader mounted on suction manifold, external to cabinet.

DOWNFLOW KIT PARTS

METAL DRAIN PANS:

- 16" DWNFLWM-16
- 18" DWNFLWM-18

PLASTIC DRAIN PANS:

- DWNFLWP



WANT MORE INFORMATION ON ASPEN'S CC SERIES EVAPORATOR COILS?

SCAN QR CODE TO VISIT THIS PRODUCT ON OUR WEBSITE



For complete warranty details, please visit our Warranty Information tab when you visit Aspen's website.

To view this coil's product information online for the most up-to-date information scan the QR Code.

In keeping with its commitment to continuous improvement, Aspen Manufacturing reserves the right to make changes without notice and incurring obligation. To stay up-to-date with this product and Aspen's trusted line of coils, air handlers, and more, go to our website. CE Spec-2025-03

SPECIFICATIONS & PERFORMANCE:

COIL MODEL	NOMINAL CAPACITY (BTUs)	CABINET DIMENSIONS				SHIPPING INFORMATION				
		MIN. WIDTH	MAX. WIDTH (W)	DEPTH (D)	HEIGHT (H)	WEIGHT (LBS)			SKID QTY	
						2 ROW	3 ROW	4 ROW		
CE24A*	24,000	14	23	21-1/2	19	31	39	46	20	
CE24B*		14	23		19	36	45	54	20	
CE24C*		14	23		23	41	52	61	12	
CE24D*		14	23		23	46	58	69	12	
CE30A*	30,000	14	23		19	36	45	54	20	
CE30B*		14	23		23	41	52	61	12	
CE30C*		14	23		23	46	58	69	12	
CE30D*		14	23		27	52	65	77	12	
CE30E*		14	23		27	54	67	79	12	
CE36A*	36,000	14 for 2, 3R; 17 for 4R	23		23	41	52	61	12	
CE36B*			23		23	46	58	69	12	
CE36C*			23		23	27	52	65	77	12
CE36D*			23		23	27	57	71	84	12
CE36F*		17	26-1/2		30	67	84	100	10	
CE42A*	42,000	17	26-1/2		23	46	58	69	12	
CE42B*		17	26-1/2		27	52	65	77	12	
CE42C*		17	26-1/2		27	57	71	84	12	
CE42D*		17	26-1/2		30	62	78	92	10	
CE48A*	48,000	17	26-1/2		27	52	65	77	12	
CE48B*		17	26-1/2		30	57	71	84	12	
CE48C*		17	26-1/2	30	62	78	92	10		
CE48D*		17	26-1/2	30	67	84	100	10		
CE48F*		17	26-1/2	30	64	80	94	10		
CE48G*		17	26-1/2	30	69	86	102	10		
CE60A*	60,000	20-1/2	26-1/2	30	62	78	92	10		
CE60B*		20-1/2	26-1/2	30	67	84	100	10		
CE60C* (3)		20-1/2	26-1/2	23	30	70	88	104	10	
CE60D* (3)		20-1/2	26-1/2	23	30	76	95	112	10	
CE60F*		20-1/2	26-1/2	21-1/2	30	64	80	94	10	

Duct opening dimensions can be ascertained by subtracting 1.50" for top opening width/depth, 3/4" for bottom opening.

Notes: 1) Not all drain pan sizes are currently available in heavy duty plastic. Check with your local Aspen representative for current availability. 2) Do not use heavy duty plastic drain pans on oil furnaces or other applications where outlet temperatures may exceed 290°F+/-5°F. Specify metal drain pans for these applications. 3) Metal drain pan. Slab rotated 90° inside cabinet. Refrigerant and plumbing connections still exit cabinet front.

DRAIN PAN TEMPERATURE TABLE	
DRAIN PAN TYPE	TEMP LIMITS
Plastic - Standard	290°
Plastic - High Temp	425°
Metal - High Temp	600°

In keeping with its commitment to continuous improvement, Aspen Manufacturing reserves the right to make changes without notice and incurring obligation. To stay up-to-date with this product and Aspen's trusted line of coils, air handlers, and more, go to our website. CE Spec-2025-03