


DM SERIES COILS FOR MANUFACTURED HOME PRODUCTS

UNCASED ALUMINUM UPFLOW/DOWNFLOW



Representative image only. Some models may vary in appearance.

STANDARD FEATURES

- Rifled aluminum tubing, enhanced aluminum fins.
- Downflow plates and manufactured housing drain hose and drain elbow included.
- Multi-stage leak testing at 500 psi pressure decay, mass spectrometer tested with Helium, then Nitrogen pressurized and factory sealed optimal system integrity and long-term reliability.
- Left-hand refrigerant/plumbing connections, with downturn suction line for easy installation in manufactured housing applications. Schrader provided for pressure assurance testing. Refrigerant and plumbing connections:
 - **Liquid line:** 3/8" ODS
 - **Suction line:**
 - ▶ 3/4" ODS on 1-1/2-ton to 3-ton
 - ▶ 7/8" ODS on 3-1/2-ton to 5-ton
 - **Drain connections:**
 - ▶ 195L pans have four (4) drains 3/4" FPT
 - ▶ 177L pans have one (1) LH 3/4" FPT
- Heavy duty polypropylene drain pans.
- AHRI certifiable with all brands of A/C and heat pump systems.
- A2L refrigerants require a Refrigerant Detection System (RDS) for compliance.
- ETL listed for R22 and R410A. ETL listed for R454B and R32 with Refrigerant Detection System (RDS).

WARRANTY

- Ten-year limited warranty with registration.

CUSTOMIZATION OPTIONS*

UNIVERSAL A2L REFRIGERANT TECHNOLOGY FOR R32 & R454B SYSTEMS



IDEAL FOR USE WITH BOTH CASED AND UNCASED COILS, PLUS ALL AIR HANDLERS!

Versa Pro coils are easily configurable for use with either R32 or R454B refrigerant with proper metering device. Utilizing universal Refrigerant Detection Systems (RDS) to ensure regulatory compliance.

OTHER POPULAR CUSTOM OPTIONS:

- Refrigerant Detection System (RDS) kit factory-installed.
- Factory or field-installed TXV available.

DOWNFLOW KIT OPTIONS:

METAL DRAIN PANS

- 16" DWNFLWM-16
- 18" DWNFLWM-18

PLASTIC DRAIN PANS

- DWNFLWP

DM-SS-C-001



R-410A • R-22 • R-454B • R-32
REFRIGERANT READY
WHEN PROPER METERING DEVICE IS USED



In keeping with its commitment to continuous improvement, Aspen Manufacturing reserves the right to make changes without notice and incurring obligation. To stay up-to-date with this product and Aspen's trusted line of coils, air handlers, and more, go to our website. © 2025 Aspen Manufacturing. All Rights Reserved

Phone: 281.441.6500 Toll Free: 800.423.9007 Fax: 281.441.6510 Customer Service: info@aspenmfg.com Warranty Team: warranty@aspenmfg.com



WWW.ASPENMFG.COM

PERFORMANCE & DIMENSIONAL DATA (In.)										
COIL MODEL	NOM. CAPACITY (BTU)	CONNECTIONS		DIMENSIONS				SHIPPING INFO.		
		LIQ. LINE	SUCT. LINE	DRAIN PAN			COIL ASMBLY HEIGHT	WEIGHT (LBS)		SKID QTY
				STANDARD WIDTH W"		DEPTH		# OF ROWS		
		OD	OD	17-3/4	19-1/2	D"	H"	3	4	
DM24A3*-177L	24,000	3/8	3/4	17-3/4(4)	-	19-5/8	13-1/2	18	-	30
DM24B3*-177L		3/8	3/4	17-3/4(4)	-	19-5/8	15-1/2	21	-	25
DM24E3*-177L		3/8	3/4	17-3/4(4)	-	19-5/8	13-1/2	18	-	30
DM24E4*-177L		3/8	3/4	17-3/4(4)	-	19-5/8	13-1/2	-	27	30
DM36A3*-177L	36,000	3/8	3/4	17-3/4(4)	-	19-5/8	17-1/2	25	-	25
DM36E3*-177L		3/8	3/4	17-3/4(4)	-	19-5/8	15-1/2	21	-	25
DM36B4*-177L		3/8	3/4	17-3/4(4)	-	19-5/8	19-1/2	-	40	20
DM36B4*-195L		3/8	3/4	-	19-1/2	19-1/2	19-1/2	-	40	20
DM36F3*-195L		3/8	3/4	-	19-1/2	19-1/2	23-1/2	42	-	12
DM36F4*-195L		3/8	3/4	-	19-1/2	19-1/2	23-1/2	-	46	12
DM42B3*-177L	42,000	3/8	7/8	17-3/4(4)	-	19-5/8	21-1/2	35	-	20
DM42E4*-177L		3/8	7/8	17-3/4(4)	-	19-5/8	19-1/2	-	40	20
DM48E3*-177L	48,000	3/8	7/8	17-3/4	-	19-5/8	19-1/2	27	-	20
DM59A4*-177L	60,000	3/8	7/8	17-3/4(4)	-	19-5/8	19-1/2	-	40	20
DM59A4*-195L		3/8	7/8	-	19-1/2	19-1/2	19-1/2	-	40	20
DM60A4*-195L		3/8	7/8	-	19-1/2	19-1/2	23-1/2	-	46	12
DM60B4*-195L		3/8	7/8	-	19-1/2	19-1/2	27-1/2	-	52	12

Notes: (1) Do not use plastic drain pans on oil furnaces or other applications where outlet temperature may exceed 290F +/- 5°F. Metal drain pans are recommended for this type of application. (2) Metal drain pan. (4) Metal drain pan applicable for 4 row coils.

DRAIN PAN TEMPERATURE TABLE	
DRAIN PAN TYPE	TEMPERATURE LIMITS
Plastic - Standard	290°
Plastic - High Temp	425°
Metal - High Temp	600°

HELPFUL LINKS



VIEW PRODUCT ONLINE

For full warranty terms and conditions, please refer to the Warranty Information section on Aspen's official website.



VIEW VERSA PRO ONLINE

Learn more about Aspen's A2L Refrigerant Technology for R32 and R454B Systems.

In keeping with its commitment to continuous improvement, Aspen Manufacturing reserves the right to make changes without notice and incurring obligation. To stay up-to-date with this product and Aspen's trusted line of coils, air handlers, and more, go to our website. © 2025 Aspen Manufacturing. All Rights Reserved

Phone: 281.441.6500 Toll Free: 800.423.9007 Fax: 281.441.6510 Customer Service: info@aspenmfg.com Warranty Team: warranty@aspenmfg.com